

## OSLO PACIFIC

### General info

Built: 2011  
 Port of Registry: Madeira  
 Flag: Portugal  
 IMO no: 9521758  
 Class: DNV  
 Owners P+I Club: Gard Oslo

### Tonnage

Dwt: 19582  
 GT/NT: 13579 / 6428  
 Displacement: 26313  
 Panama net: 11400  
 Suez net: 11583.60

### Type

Bulk Carrier

### Dimensions

LOA: 149.96 m  
 LPP: 140.80 m  
 Beam: 23.60 m  
 Draft Summer: 9.39 m  
 Depth moulded: 12.50 m  
 WLTHC:

### Engine

Main engine: MAN B&W 5S50MC-C  
 6570 Kw x 127 rpm  
 Aux. Engine: 3 x Wartsila W4L20  
 1 x AE 680 kW x 900 rpm  
 2 x AEs 548 kW x 900 rpm  
 Shaft generator: -  
 Bow thruster: SCANA type 600 kW

### Tank capacity

Fuel IFO: 1197 m3  
 Fuel GO: 204.2 m3  
 Fresh water: 242.7 m3  
 Ballast: 7995.1 m3

### Containers

NIL

### IMDG dangerous cargoes

Vessel is fitted for the carriage of the following IMDG goods classes in bulk – 4.1, 4.2, 4.3, 5.1, 9

### Capacity

Grain 22192 cbm

### Holds Capacity Grain /(M3/CUFT):

1) 3445,9 / 121690,8  
 2) 4745,0 / 167568,1  
 3) 4744,0 / 167568,1  
 4) 4793,1 / 169266,7  
 5) 4463,5 / 157627,0

### Holds

Number of Holds: 5

### Hold dimensions (L X B):

H1 - 19.2 X 11.20(FORE)/19.7(AFT)  
 H2 - 21.6 X 19.7  
 H3 - 21.6 X 19.7  
 H4 - 21.6 X 19.7  
 H5 - 20.0 X 19.7(FORE)/12.60(AFT)

Height of all cargo holds: 10.8 m

### Hatch

#### Hatch openings dimensions:

H1 - 12.8 X 12.8 X 1.95  
 H2 - 14.4 X 19.7 X 1.95  
 H3 - 14.4 X 19.7 X 1.95  
 H4 - 14.4 X 19.7 X 1.95  
 H5 - 14.4 X 19.7 X 1.95

Type of covers: hydraulic folding type hatch covers

### Permissible Loads

Tanktop: 20,0 mt/sqm

The allowable maximum bulk cargo density is 3.0t/ m3.

The steel coil load 20 tonnes (diameter 1.5m with length 1.5m) x2 tiers, with three (3) dunnage under one coil

Vessel is not allowed to load cargo on deck and hatch covers

### Hold Equipment

St Lawrence fitted: Yes

Tween deck pontoons: No

CO2 / smoke detector fitted: Yes

Marine dehumidifier of cargo holds: Yes

Mechanical ventilation of cargo holds: Yes (6 changes per hour basis empty holds)

### Gear

Type of gear: 3 x McGregor electric slewing cranes with SWL 30 tons each

SWL: 30 tons at outreach 4 – 22.0 m  
 24 tons in Grab mode